

MOISTURE ANALYZER ANA21-110C



MOISTURE ANALYZER ANA21-110C

Moisture Analyzer measures the amount of moisture in a substance which particularly helps in food processing. These analyzers are also commonly used in environmental, pharmaceutical, and materials science labs. We provide a variety of moisture analyzer according to applications, features and customers requirements.

Used in Food processing, Environmental, Pharmaceutical, Laboratory, Research, Medical, Hospitals, Agriculture, Industrial.

Also known as Laboratory Moisture Analyzer, Moisture Balance, Moisture Meter, Halogen Moisture analyzer, Laboratory Moisture Balance, Laboratory moisture Meter, Laboratory Halogen Moisture analyzer.

ANA21-110C MOISTURE ANALYZER

Halogen Heating

Pan size: ϕ 100mm

3.7 inch touch screen

Long distance operated

Stainless steel chamber

Easy cleaning after testing

Temperature and time can be set

The percentage of moisture content

Max 230 degree heating temperature

Automatic opens the heating chamber



SPECIFICATIONS

Model	ANA21-110C
Weighing Range	110 g
Temperature	40°C-230°C
Operating Temperature Range	5°C-35°C
Temperature Set	1°C
Temperature Setting	40°C-230°C By 1°C Step
Moisture Range	0.00%-100.0%
Moisture Readability	0.0001
Dry Range	100.00%-0.00%
Dry Residual Readability	0.0001
Pan Size	Φ 100 mm
Readability	0.001 g
Interface	Cable, RS232/RJ45/USB
Heat Source	HALOGEN LAMP
Calibration	External Calibration
Rechargeable Battery	No
Temperature Sensor	PT-100
Display	7 inch touch panel
Operation Height	275 mm
The Chamber Height	35 mm
Time Setting	1-99 min By 10 s

Dimension	215x195x415 mm
Indicator Dimension	200x75x135 mm
Number of History	20
Number of Storage	20
Power	400 W
Balance	Output: 9 V
Machine	Output: 24 V (Dual-drive)
Power Supply	220 V± 15%, 110 V± 15% / 50 Hz, 60 Hz



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com