

VERTICAL AUTOCLAVE AUT033-075



VERTICAL AUTOCLAVE AUT033-075

AUT033-075 VERTICAL AUTOCLAVE

- Three times pre-vacuum
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- LED touch screen display
- Standard test interface
- Self-expanding seal
- With drying function
- With stainless steel bucket or basket
- With automatic protection function over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning.
- Automatic water
- External steam Generator
- Buzzer reminder after sterilization, automatic stop.
- Automatic discharge of cold air, automatic steam exhaust after sterilization
- Internal printer



SPECIFICATIONS

Model	AUT033-075
Capacity	75 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 400x655
Bucket dimension	Ø 380x560
Basket dimension	Ø 360x280x2
Outer dimension	725x525x1170
Packing size	840x610x1310
Net weight	124 Kg
Gross Weight	150 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com