

VERTICAL AUTOCLAVE AUT034-050



VERTICAL AUTOCLAVE AUT034-050

AUT034-050 VERTICAL AUTOCLAVE

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- With drying function
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With automatic protection function over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- Automatic discharge of cold air, automatic steam exhaust after sterilization, Internal steam cycle



SPECIFICATIONS

Model	AUT034-050
Capacity	50 L
Power	3.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 350x525
Bucket dimension	Ø 330x460
Basket dimension	Ø 320x240x2
Outer dimension	630x500x1180
Packing size	800x600x1230
Net weight	112 Kg
Gross Weight	130 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com