

# VERTICAL AUTOCLAVE AUT035-100



# VERTICAL AUTOCLAVE AUT035-100

## AUT035-100 VERTICAL AUTOCLAVE

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Yr Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With drying function
- With automatic protection function:over temperature protection; over pressure protection; low water level protection; anti dry burning
- With stainless steel bucket or basket Buzzer reminder after sterilization, automatic stop
- Automatic discharge of cold air,automatic steam exhaust after sterilization



## SPECIFICATIONS

Model	AUT035-100
Capacity	100 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 450x650
Bucket dimension	Ø 420x540
Basket dimension	Ø 410x300x2
Outer dimension	550x550x1250
Packing size	690x650x1410
Net weight	106 Kg
Gross Weight	133 Kg

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)