

VERTICAL AUTOCLAVE AUT036-035



VERTICAL AUTOCLAVE AUT036-035

AUT036-035 VERTICAL AUTOCLAVE

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With automatic protection function: over temperature protection; over pressure self discharge protection; low water level protection; anti dry burning
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- Automatic discharge of cold air, automatic steam exhaust after sterilization



SPECIFICATIONS

Model	AUT036-035
Capacity	35 L
Power	3.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 350x400
Bucket dimension	Ø 330x320
Basket dimension	Ø 320x350
Outer dimension	480x480x1000
Packing size	580x630x1130
Net weight	58 Kg
Gross Weight	79 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com