

VERTICAL AUTOCLAVE AUT037-035



VERTICAL AUTOCLAVE AUT037-035

AUT037-035 VERTICAL AUTOCLAVE

Bolt structure

High quality stainless steel material

Microcomputer automatic control, arbitrary set of sterilization parameters

Digital display and touch buttons

Standard test interface

The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning

With stainless steel bucket or basket

Buzzer reminder after sterilization, automatic stop.

Automatic cooling air, sterilization end automatic exhaust steam



SPECIFICATIONS

Model	AUT037-035
Capacity	35 L
Power	2.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 300x500
Bucket dimension	Ø 280x400
Outer dimension	400x400x860
Packing size	550x500x1030
Net weight	41 Kg
Gross Weight	58 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com