

# VERTICAL AUTOCLAVE AUT037-075



# VERTICAL AUTOCLAVE AUT037-075

## AUT037-075 VERTICAL AUTOCLAVE

Bolt structure

High quality stainless steel material

Microcomputer automatic control, arbitrary set of sterilization parameters

Digital display and touch buttons

Standard test interface

The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning

With stainless steel bucket or basket

Buzzer reminder after sterilization, automatic stop.

Automatic cooling air, sterilization end automatic exhaust steam



## SPECIFICATIONS

Model	AUT037-075
Capacity	75 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 400x625
Bucket dimension	Ø 380x560
Basket dimension	Ø 360x280x2
Outer dimension	525x525x1060
Packing size	630x680x1190
Net weight	61 Kg
Gross Weight	82 kg

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)