

VERTICAL AUTOCLAVE AUT037-100



VERTICAL AUTOCLAVE AUT037-100

AUT037-100 VERTICAL AUTOCLAVE

Bolt structure

High quality stainless steel material

Microcomputer automatic control, arbitrary set of sterilization parameters

Digital display and touch buttons

Standard test interface

The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning

With stainless steel bucket or basket

Buzzer reminder after sterilization, automatic stop.

Automatic cooling air, sterilization end automatic exhaust steam



SPECIFICATIONS

Model	AUT037-100
Capacity	100 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 450x650
Bucket dimension	Ø 420x540
Basket dimension	Ø 410x300x2
Outer dimension	555x555x1080
Packing size	690x650x1230
Net weight	78 Kg
Gross Weight	103 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com