

# VERTICAL AUTOCLAVE AUT037-120



# VERTICAL AUTOCLAVE AUT037-120

## AUT037-120 VERTICAL AUTOCLAVE

Bolt structure

High quality stainless steel material

Microcomputer automatic control, arbitrary set of sterilization parameters

Digital display and touch buttons

Standard test interface

The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning

With stainless steel bucket or basket

Buzzer reminder after sterilization, automatic stop.

Automatic cooling air, sterilization end automatic exhaust steam



## SPECIFICATIONS

Model	AUT037-120
Capacity	120 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 450x760
Bucket dimension	Ø 420x660
Basket dimension	Ø 410x350x2
Outer dimension	555x599x1200
Packing size	690x650x1330
Net weight	82 Kg
Gross Weight	108 Kg

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)