

VERTICAL AUTOCLAVE AUT037-150



VERTICAL AUTOCLAVE AUT037-150

AUT037-150 VERTICAL AUTOCLAVE

Bolt structure

High quality stainless steel material

Microcomputer automatic control, arbitrary set of sterilization parameters

Digital display and touch buttons

Standard test interface

The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning

With stainless steel bucket or basket

Buzzer reminder after sterilization, automatic stop.

Automatic cooling air, sterilization end automatic exhaust steam



SPECIFICATIONS

Model	AUT037-150
Capacity	150 L
Power	6.0 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Chamber volume	Ø 500x780
Bucket dimension	Ø 470x720
Basket dimension	Ø 460x350x2
Outer dimension	605x649x1210
Packing size	750x700x1370
Net weight	90 Kg
Gross Weight	116 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com