

HORIZONTAL AUTOCLAVE AUT21-150



HORIZONTAL AUTOCLAVE AUT21-150

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT21-150 HORIZONTAL AUTOCLAVE

High Quality Stainless steel chamber with drying function

Safety features for over temperature and pressure

Automatic opening of safety valve if pressure exceeds 0.165 MPa

Door remains locked if pressure exceeds 0.027MPa

Over temperature, over pressure, auto protection device

Automatic power cut off and water cut off in case of water shortage



SPECIFICATIONS

| | |
|---------------------------|----------------------|
| Model | AUT21-150 |
| Capacity | 150 L |
| Adjustment of Temperature | 105°C - 134°C |
| Sterilization Temperature | 134°C |
| Sterilization Time | 0-60 min |
| Heat Average | ±1°C |
| Working Pressure | 0.22 MPa |
| Time of Drying | 0-60 min |
| Chamber Dimension | 440x1000 mm |
| Overall Dimension (LxWxH) | 1400x600x1300 mm |
| Packing Size | 1550 x 750 x 1850 mm |
| Weight | 240/320 kg |
| Power | 9000 W |
| Power Supply | 380 V, 50Hz |

PROGRAM

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com