LABSTAC

PORTABLE AUTOCLAVE AUT41-24

labstac.com

PORTABLE AUTOCLAVE AUT41-24

Portable Autoclave is used for general purpose sterilization. Saturated steam is used to sterilize articles rapidly and efficiently. It is also used as a cooker in plateau areas and also for making high quality drinking water in Drinking Water Plant.
Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research..
Also known as Portable Sterilizer, Steam Autoclave Sterilizer, Portable Autoclave, Pressure Steam Sterilizer, Portable Pressure Steam Sterilizer, Dental Autoclave.

AUT41-24 PORTABLE AUTOCLAVE

SPECIFICATIONS

Model	AUT41-24
Capacity	24 L
Function	Electric or LPG heated.
Sterilization Temperature	126°C
Working Pressure	0.14-0.16 Mpa
Maximum Working Pressure	0.165 Mpa
Chamber Dimension	280x390mm
Overall Dimension (LxWxH)	410x410x550 mm
Chamber Material	Stainless Steel
Weight	15/17 kg
Power	2 KW
Power Supply	220 V, 50 Hz

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com