

PORTABLE AUTOCLAVE AUT43-24



PORTABLE AUTOCLAVE AUT43-24

Portable Autoclave is used for general purpose sterilization. Saturated steam is used to sterilize articles rapidly and efficiently. It is also used as a cooker in plateau areas and also for making high quality drinking water in Drinking Water Plant.

Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research..

Also known as Portable Sterilizer, Steam Autoclave Sterilizer, Portable Autoclave, Pressure Steam Sterilizer, Portable Pressure Steam Sterilizer, Dental Autoclave.

AUT43-24 PORTABLE AUTOCLAVE

SPECIFICATIONS

Model	AUT43-24
Capacity	24 L
Function	Electric heated
Sterilization Temperature	126°C
Steam Exhausting Temperature	≤1°C
Working Pressure	0.14-0.16Mpa
Maximum Working Pressure	0.165 Mpa
Timer Range	0-99min
Chamber Dimension	270x500mm
Overall Dimension (LxWxH)	440x420x750 mm
Chamber Material	Stainless Steel
Weight	14/15 kg
Power	2 KW
Power Supply	220 V, 50 Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com