

LOW TEMPERATURE CIRCULATOR BAC025-10



LOW TEMPERATURE CIRCULATOR BAC025-10

BAC025-10 LOW TEMPERATURE CIRCULATOR

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C

Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total



SPECIFICATIONS

Model	BAC025-10
Capacity	15.5 L
Temperature range	-20 - 20°C
Temperature accuracy	±2°C
Cooling capacity at 10°C	1500 W
Refrigerant	R410A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1300 W
Power requirements	AC 220 V / 50 HZ
Pump power	60
Pump flow max.	17 L / min
Maximum head	15 m
Inlet/Outlet pipe diameter	Φ12 mm
Weight	60
Liquid storage	13
Noise level	≤55
Dimension	400Wx500Dx739H mm

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@mail.labstac.com | Website: labstac.com