

# WATER BATH BAC028-12



# WATER BATH BAC028-12

## BAC028-12 WATER BATH

PID temperature controller, large LCD display screen and interface provides for userfriendly operation

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

The standard stainless-steel bottom plate, helps prevents direct contact by accessories and tubes to heating element and sensors

Drain valve makes emptying of bath water fast and easy for cleaning and moving



## SPECIFICATIONS

Model	BAC028-12
Capacity	12 L
Power requirements	AC 220 V 50 HZ
Power	800 W
Temperature Range	RT+5 - 100°C
Temperature fluctuation	±0.2°C
Temperature resolution	0.1°C
Internal dimension	305Wx150Dx240H mm
External dimension	353Wx340Dx265H mm
Timer	1 - 5999 min
Net weight	12 Kg
Porous cover(lid)	4 - hole

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)