

# SHAKING WATER BATH BAC031-33



# SHAKING WATER BATH BAC031-33

## BAC031-33 SHAKING WATER BATH

Microprocessor temperature controller with LCD screen ensures precise and reliable control, easy to operate

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

Programming setting function with 7 periods and 9 steps for each period, which means there are 63 programmable steps in total

Easy to set adjustable timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Drain valve makes emptying of bath water fast and easy for cleaning and moving



## SPECIFICATIONS

Model	BAC031-33
Capacity	33 L
Temperature range	RT+5 - 99°C
Display resolution	0.1°C
Temperature uniformity (at 37°C)	±1.0°C
Shaking speed range	30 - 180 rpm
Amplitude	30mm (Standard) or 40mm (Option)
Interior dimension	438Wx310Dx250H mm
Exterior dimension	643Wx350Dx353H mm
Power requirements	AC 220 V 50 HZ
Power consumption	1250 W

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)