

DRY BATH INCUBATOR BAC11-100



DRY BATH INCUBATOR BAC11-100

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath.

BAC11-100 DRY BATH INCUBATOR

Microprocessor intelligent control

The unique design, Special plastic on the external edge of wash tank which is anti-corrosion, anti-scald

Stainless steel interior

Built-in frequency scanning function

Water level control

High ultrasound power and low noise



SPECIFICATIONS

Model	BAC11-100
Temperature Range	RT+5-100 °C
Temp. Setting Range	5 °C~100 °C
Temp. Stability@37°C	±0.3 °C
Block Temp. Uniformity	±0.5 °C
Temp. Display Accuracy	0.1 °C
Heating Speed	≤15min (20 °C to 100 °C)
Time Range	1 min~9999 min
Voltage	AC 220 V/AC 110 V, 50/60 Hz
Power	150 W
Fuse	250 V, 1A/2A, φ5x20
Dimension	W.156 x D.176 x H.121 mm
Net Weight	1.5 kgs

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Dimension
1702005005	Block A	96 x 0.2ml	Φ104.5mm x 32
1702005006	Block B	59 x 0.5ml	Φ104.5mm x 32
1702005007	Block C	39 x 1.5ml	Φ104.5mm x 32
1702005008	Block D	39 x 2.0ml	Φ104.5mm x 32
1702005009	Block E	18 x 5.0ml	Φ104.5mm x 32

1702005010	Block F	24 x 0.5ml + 30 x 1.5ml	Φ104.5mm x 32
------------	---------	-------------------------	---------------

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com