

DRY BATH INCUBATOR BAC17-100



DRY BATH INCUBATOR BAC17-100

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Pharmaceutical, Chemical, Food Safety, Environment, Quality inspection, Laboratory.

Also known as Laboratory Dual Temperature Dry Bath Incubator.

BAC17-100 DRY BATH INCUBATOR



SPECIFICATIONS

Model	BAC17-100
Capacity	10 L
Function	Power adjustable
Temperature Range	R.T.+5 °C~100 °C
Temperature Control Accuracy	±0.5°C
Cleaning Tank (LxWxH)	300x240x150 mm
Outer Dimension (WxDxH)	420x310x370 mm
Weight	3 kg
Maximum Input Power	400
Maximum Output Power	360
Heating Power	NO
Power Adjustable (%)	30-100
Drain	YES
Level Control System	YES

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com