

DRY BATH INCUBATOR BAC19-04



DRY BATH INCUBATOR BAC19-04

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Pharmaceutical, Chemical, Food Safety, Environment, Quality inspection, Laboratory.

Also known as Laboratory Dual Temperature Dry Bath Incubator.

BAC19-04 DRY BATH INCUBATOR

Fast heating speed, uniform heating, accurate temperature control, high stability, low energy consumption and no noise.

Built in temperature calibration function, automatic fault detection and buzzer alarm function.

Built in over-temperature protection device, safe and reliable, enhance the service life of the machine.

Product designed compact and tight, occupied little space. Using freer and easier.

Various blocks for convenient replacement, easy for cleaning and disinfection.



SPECIFICATIONS

Model	BAC19-04
Temp. Control Range	4 °C constant
Temp. Setting Range	4°C
Temp. Stability@4°C	±0.5°C
Block Temp. Uniformity	±0.5°C
Cooling Speed	≤10min(Depending on blocks)
Voltage	AC90~230V, 50/60Hz
Power	100W
Fuse	250V, 3A, φ5x20
Dimension	W.196 x D.270 x H.170mm
Net Weight	3.5kgs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@mail.labstac.com | Website: labstac.com