

# MICRO-PLATE INCUBATOR BAC1A-04



# MICRO-PLATE INCUBATOR BAC1A-04

Labstac Micro-plate incubator features a well-designed micro processing technique and is well combined with PID controlling system.

Used in Widely used for solution incubation of ELISA plate (96-well/384-well), cell culture plate (24-well / 48-well / 96-well) at proper temperature or cell-based assays, bacterial culturing, incubation and thermal degradation of proteins and nucleic acids in the areas of microbiology, molecular diagnostics, and biological sciences..

Also known as Microplate Incubator Shakers.

## BAC1A-04 MICRO-PLATE INCUBATOR

LCD display. Setting temperature and actual temperature simultaneously displayed.  
Diminishing time displayed.

Friendly human-machine operation interface. Streamline shape, pretty and elegant.  
Convenient for cleaning.

Uniformly upper & down heating for samples in micro plates. The experiment effect is exact correspondence of the setting and actual temperature.

Microprocessor controls temperature and time, good temperature control linear, small fluctuations.

4 standard ELISA plates and microplates can be placed, and sound alarm signal after the program finished.



## SPECIFICATIONS

Model	BAC1A-04
Temp. Control Range	R.T.+5°C ~70°C
Temp. Setting Range	5°C ~70°C
Temp. Stability@37°C	±0.2°C
Platform Temp. Uniformity	±0.5°C
Temp. Display Accuracy	0.1°C
Heating Speed	<25min (20°C to 70°C)
Time Range	1min~99h59min
Sample Capacity	4 Pieces of Plates(Height<40mm)
Voltage	AC 220V/AC 110V, 50/60Hz
Power	250W
Fuse	250V, 3A/5A, φ5x20
Dimension	W.345 x D.310 x H.178mm
Net Weight	4.9kgs

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)