

# DRY BATH INCUBATOR BAC1D-120



# DRY BATH INCUBATOR BAC1D-120

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Calibration tests, High temperature organic distillation, External circulation, High temperature experiments. Also known as Bath Circulator, Laboratory Bath Circulator.

## BAC1D-120 DRY BATH INCUBATOR

Microprocessor temperature controller

Easy maintenance

LCD display with touch key panel for temperature setting

Over temperature alarm system



## SPECIFICATIONS

Model	BAC1D-120
Temperature Range	Room temp.-120°C
Temperature Uniformity	±0.5°C
Outer Dimension (WxDxH)	95Wx150Dx50H mm
Weight	3 kg
Temperature Control Accuracy	±0.5°C
Overheating protection	140°C
Adapter block material	Aluminium
Display	LED
Power	160 W
Power Supply	100-120 V / 220-240 V ,50 Hz / 60 Hz

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)