

AIR BATH BAC21-060



AIR BATH BAC21-060

It is widely used in preservation and reactions of samples, DNA amplification, and initial denaturation of electrophoresis and so forth. The LCD display is very easy to setup and use, and it is quite compact.

Used in High temperature organic distillation, External circulation, Calibration tests, High temperature experiments, Laboratory.

Also known as Cooling Bath Circulator, Refrigerated Circulator, Laboratory Refrigerated Bath Circulator.

BAC21-060 AIR BATH



SPECIFICATIONS

Model	BAC21-060
Temp. Control Range	R.T.+5°C~60°C
Temp. Setting Range	5°C~60°C
Temp. Stability@37°C	±0.2°C
Temp. Uniformity	±0.5°C
Temp. Display Accuracy	0.1°C
Time Range	1min~99h59min
Fan Speed Range	1200~3200rpm
Incubation Space Size	L.245 x W.215 x H.85mm
Voltage	AC 220V/AC 110V, 50/60Hz
Power	300W
Fuse	250 V, 2A/4A, φ5x20
Dimension	W.275 x D.395 x H.150mm
Net Weight	8.1 kgs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com