

# DUAL TEMPERATURE CONTROL DRY BATH INCUBATOR BAC34-110HC



# DUAL TEMPERATURE CONTROL DRY BATH

## INCUBATOR BAC34-110HC

Product designed compact and tight, occupy little space and has excellent performance, it is a good replacement for the traditional water bath devices. Used in the fields of pharmaceutical, chemical, food safety, environment, and quality inspection. Due to its features like fast heating speed, uniform heating, accurate temperature control, high stability, low energy consumption and no noise makes it an ideal choice.

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis, Laboratory.

Also known as Digital Heating Block, Laboratory Mini Dry Bath Incubator.

## BAC34-110HC DUAL TEMPERATURE CONTROL DRY BATH INCUBATOR



### SPECIFICATIONS

Model	BAC34-110HC
Temperature Range	Heating: Room temp.-110°C Cooling: Room temp.~below room temp. 25°C
Temperature Uniformity	Max. $\pm 0.5^{\circ}\text{C}$ (@20°C-25°C)
Outer Dimension (WxDxH)	200Wx235Dx120H mm
Weight	7.3 kg
Temperature Control Accuracy	$\pm 0.5^{\circ}\text{C}$ (@20°C-45°C)
Overheating protection	150°C
Adapter block material	Aluminium
Display	TFT
Power	200 W
Power Supply	100-120 V / 220-240 V ,50 Hz / 60 Hz



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)