LABSTAC

DUAL TEMPERATURE CONTROL DRY BATH INCUBATOR BAC36-100

labstac.com

DUAL TEMPERATURE CONTROL DRY BATH INCUBATOR BAC36-100

Product designed compact and tight, occupy little space and has excellent performance, it is a good replacement for the traditional water bath devices. Used in the fields of pharmaceutical, chemical, food safety, environment, and quality inspection. Due to its features like fast heating speed, uniform heating, accurate temperature control, high stability, low energy consumption and no noise makes it an ideal choice.
Used in Immunoassays,Melting points, Enzyme reactions, Boiling points, Incubation, Activation of cultures, Laboratory procedures..
Also known as Digital Dry Bath Incubator, Heating block, Laboratory Dry Bath Incubator.

BAC36-100 DUAL TEMPERATURE CONTROL DRY BATH INCUBATOR

SPECIFICATIONS

Model	BAC36-100
Temperature Range	0-100 °C
Temperature Uniformity	±0.5 °C
Weight	1.4 kg
Temperature Precision	±0.5°C
Operation Ambient Temperature	8-30°C
Power Supply	12 V DC, 7A

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com