

MINI DRY BATH INCUBATOR BAC43-099



MINI DRY BATH INCUBATOR BAC43-099

It is a micro-processor controlled heating block with heater or semiconductor refrigeration technology. It provides safe, compact, dry heat for a wide variety of clinical and general chemistry applications to give you reproducible results. Mostly used in preservation and reactions of sample, DNA amplification and initial denaturation of electrophoresis and so forth.

Used in High temperature organic distillation, External circulation, Calibration tests, High temperature experiments, Laboratory.

Also known as Cooling Bath Circulator, Refrigerated Circulator, Laboratory Refrigerated Bath Circulator.

BAC43-099 MINI DRY BATH INCUBATOR

Fuzzy PID temperature control system: control temperature stability accurately and fast.

Multi-protection: Over-current protection, high and low temperature warning functions, dry-running protection.

Convenience function: Parameters memory function, temperature correction.

ECO-refrigerant R134a and high quality compressor guarantee the cooling system ecofriendly and powerful

Low Noise design: use high quality compressor and mute pump.

Robust water tank: ultra-slushing and rust-proof

Bright LCD temperature display

Compact design, removable venting grid for convenient cleaning to maintain cooling performance and drain off water



SPECIFICATIONS

Model	BAC43-099
Temperature Range	RT+5-99.9°C
Temperature Stability	0.2°C
Display Accuracy	0.1°C
Outer Dimension (WxDxH)	360x180x150 mm
Weight	3 kg
Temperature Control Accuracy	≤0.5°C
Power	120 W
Power Supply	12 V DC

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com