

MINI DRY BATH INCUBATOR BAC45-100



MINI DRY BATH INCUBATOR BAC45-100

It is a micro-processor controlled heating block with heater or semiconductor refrigeration technology. It provides safe, compact, dry heat for a wide variety of clinical and general chemistry applications to give you reproducible results. Mostly used in preservation and reactions of sample, DNA amplification and initial denaturation of electrophoresis and so forth.

Used in High temperature organic distillation, External circulation, Calibration tests, High temperature experiments, Laboratory.

Also known as Cooling Bath Circulator, Refrigerated Circulator, Laboratory Refrigerated Bath Circulator.

BAC45-100 MINI DRY BATH INCUBATOR

PID controller offers precise temperature control and uniformity

Corrosion resistant inner and outer chamber made of stainless steel

Dual LED screen displays temperature and time

Protection against compressor overload, high/low voltage and current

Convenient and reliable operation

Equipped with caster for easy installation



SPECIFICATIONS

Model	BAC45-100
Temperature Uniformity	±0.5°C
Outer Dimension (WxDxH)	130x395x95 mm
Weight	2.25 kg
Temperature Precision	±0.5°C
Operation Ambient Temperature	8-30°C
Power Supply	12 V DC, 7A



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com