

WATER BATH BAC81-300



WATER BATH BAC81-300

Labstac Water bath provides precise temperature control along with stirring mixture function to create a stable temperature environment for a variety of applications. Easy to use and maintain, seamless stainless steel chamber with available with a digital operating system.

Used in Enzyme reactions, Immunoassay, Incubation, Laboratory, Research, Medical, Pharmaceuticals.

Also known as Laboratory water bath.

BAC81-300 WATER BATH

Unique and novel appearance, small size, powerful functions.

All surface that contact with water adopt stainless steel material and PC material, with strong corrosion resistance.

With one hole and volume of 2 liter.

Using microcomputer program PID automatic temperature control, uniform temperature control, high precision.

Built-in water level sensor, to prevent the hidden dangers of dry burning, safe and reliable.



SPECIFICATIONS

Model	BAC81-300
Time Range	1~99h59min (0 is forever)
Temperature Range	RT.+5°C~100°C
Temp. accuracy	±0.5°C
Temp. Uniformity@37°C	±0.5°C
Number of holes	1
Volume	2Lx1
Workspace	140x126x95mmx1
Voltage	AC 220V 50/60Hz
Power	300W
Dimensions	W.198xD.290xH.240mm
Net weight	2.3kgs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@m.labstac.com | Website: labstac.com