

PCR CABINET BSC41-400A



PCR CABINET BSC41-400A

It is designed to provide a controlled environment for the manipulation and amplification of DNA and RNA. From Dead-Air boxes to Laminar Flow UV Cabinets with HEPA filtration we have a solution to support your application. Safety is kept in mind for changing the filter.

Used in Research, Clinical laboratories, Hospital, Genetics, Microbiological.

Also known as PCR Hood, PCR Workstation.

BSC41-400A PCR CABINET

Global exclusive

Small dimension, save space, economical and convenient.

Automatic air speed adjustable with filter block.

With memory function in case of power-failure.

Interlock function: UV lamp and front window; UV lamp and blower, fluorescent lamp; Blower and front window

Audio and visual alarm: Filter replacement, window over height, abnormal air flow velocity etc

Time reserve function: This can set the UV lamp and fan working time



SPECIFICATIONS

Model	BSC41-400A
Type	PCR Cabinet
Reagent Preparation Area	Airflow Velocity - 0.3-0.45 (m/s) Airflow Volume - 290-430 (m3/h) Exhaust Type - / Pressure - Positive Operating Area Size (LxWxH) - 640x560x510 mm
Specimen Preparation Area	Airflow Velocity - Downflow: 0.33±0.025 (m/s) Inflow: 0.53±0.025 (m/s) Airflow Volume - 250 (m3/h) Exhaust Type - TypeA2, 30% exhaust, 70% recirculation Pressure - Negative Operating Area Size (LxWxH) - 660x560x510 mm
Amplification Analysis Area	Airflow Velocity - ≥0.4 (m/s) Airflow Volume - ≥180 (m3/h) Exhaust Type - 100% exhaust Pressure - Negative Operating Area Size (LxWxH) - 640x560x510 mm
ULPA Filter	Four ,99.999% efficiency at 0.12µm.
Clean Level	Class 100, Except Amplification Analysis Area
Front Window	Manual, Toughened glass, Anti UV
Max opening	400 mm
Noise	≤67 dB (A)
Vibration	≤ 5µm
UV Lamp	15W x3, UV timer, UV life indicator
LED Lamp	8W x6
Illumination	≥650 (Each area)
Display	Touch Screen
Control System	Microprocessor
Waterproof Socket	The load of two sockets (Each area): 500W, total 6 sockets
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity
Work Surface height	750 mm

Material	Work Zone Material: 304 stainless steel Main Body Material: Cold-rolled steel with anti-bacteria powder coating
Standard Accessory	LED lamp x6 UV lamp x4, Windproof plate x2, Waterproof sockets x6
External Size (WxDxH)	2100x710x2000 mm
Package Size (WxDxH)	2250x980x1400 mm
Gross Weight	450 Kg
Consumption	600W, total 2100W (With load)
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com