

# AIR SHOWER BOX BSC51-600



# AIR SHOWER BOX BSC51-600

It is necessary passage for people entering clean room in order to minimize particulate contamination  
Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.  
Also known as Pass Box.

## BSC51-600 AIR SHOWER BOX

Photoelectric sensor, automatic blowing

Adapt with circulation wind to ensure the cleanness of shower area under non-shower status

Double door by electric interlock

LED display with adjustable blowing time(0-99s)

HEPA filter, Class 100 cleanness

### SPECIFICATIONS

Model	BSC51-600
Clean Air Speed	0.36~0.54m/s
UV Lamp	15Wx1
External Size (WxDxH)	760x670x1100 mm
Internal Size (WxDxH)	600x600x600 mm
Material	304 stainless steel
Interlock	Electronical
HEPA Filter	Efficiency $\geq 99.995\%$ at $0.3\mu\text{m}$
Gross Weight	100 kg
Packing Size(WxDxH)	880x800x1350mm
Power Supply	220V, 50Hz; 110V, 50/60Hz

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)