

AIR SHOWER BSC71-1100



AIR SHOWER BSC71-1100

Air shower is a necessary passage for people entering clean room in order to minimize the amount of particulate contaminant, to achieve workplace strict clean purification standards Personnel move through the air shower while particulate contaminants are blown off by the clean high-speed air. Then the dust cannot be brought into clean air Used in Laboratory, Microbiological, Research ,University ,.

Also known as Personal Cleaning Booth.

BSC71-1100 AIR SHOWER

Photoelectric sensor, automatic blowing

Adopt with circulation wind to ensure the cleanness of shower area under non-shower status

Double door by electric interlock

LED display with adjustable blowing time (0-99s)

HEPA filter, Class 100 cleanness



SPECIFICATIONS

| | |
|-----------------------------|---|
| Model | BSC71-1100 |
| External Size (WxDxH) | 1500x1000x2050 mm |
| Internal Size (WxDxH) | 800x900x1930 mm |
| HEPA filter | 99.995 % efficiency at 0.3 μ m |
| Spraying Wind Speed | 25 m/s |
| Air Shower time | 0-99 s (adjustable) |
| No. of SS Nozzels | 12 |
| Fluorescent Lamp | 12Wx1 |
| Consumption | 1100 W |
| Cabinet Material (Optional) | 1.Full cold-rolled steel with powder coating 2.Internal stainless steel, external with cold-rolled steel 3.Full stainless steel |
| Door Material (Optional) | 1.Cold-rolled steel with powder coating 2.Stainless steel |
| Chassis | Stainless Steel |
| Power Supply | AC220 V \pm 10%,50/60 Hz ; 110 V \pm 10%, 60 Hz |
| Gross Weight | 400 kg |
| Package Size (WxDxH) | 1600x1200x2200 mm |

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com