

# CLASS II BIOLOGICAL SAFETY CABINET BSC81-420A2



# CLASS II BIOLOGICAL SAFETY CABINET

## BSC81-420A2

It operates with a negative air pressure for personnel protection and HEPA filtered laminar airflow for product protection to meet the requirements for the environment from microorganisms and aerosols. Features like Time reverse function, Interlock function, low noise and Filter Life Indicator makes the product beneficial and reliable. Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory. Also known as Class II BSC, Biosafety Cabinet.

## BSC81-420A2 CLASS II BIOLOGICAL SAFETY CABINET

The operation perspective is wide and more humanized

Time reserve function

ULPA filter life and UV life indicator

Motorized front window

With memory function in case of power-failure

Audio and visual alarm (Abnormal airflow velocity; Filter replacement; Front window at unsafe height; High filter pressure alarm ).

Self-locking button switch to solve the trouble of losing the key

7 inch Large touch screen with Intelligent control system: Operators can check detailed status of the cabinet, such as inflow and downflow velocity, work area temperature and humidity, filter pressure, UV working time and filter working time, filter life indicator etc

Remote control: all functions can be realized with it, making the operation much easier and more convenient

Interlock function: UV lamp and front window; UV lamp and blower, LED lamp; blower and front window

Foot switch: adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement



## SPECIFICATIONS

Model	BSC81-420A2
Type	Class II, Type A2
Inflow Velocity	0.53±0.025 m/s
Down Flow Velocity	0.33±0.025 m/s
Filter	ULPA Filter - Two, 99.9995% efficiency at 0.12µm. Filter life indicator.
Max Opening	420 mm(17")
Tested Opening	Safety Height 200mm (8")
Airflow System	70% air recirculation, 30% air exhaust
Control System	Microprocessor
Work Zone Material	304 stainless steel
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Surface Height	750mm (Size can be customized according to requirements)
Front Window	Motorized. Two-layer laminated toughened glass ≥ 6mm. Anti UV.
Caster	Footmaster caster

Display	7 inch touch screen display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.
Noise	≤ 67dB
UV Lamp	30W x1, UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination.
LED Lamp	LED lamp, 12W x2
Illumination	≥1000Lux
Visual and Audio Alarm	Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm.
Waterproof Socket	Two, total load of two sockets: 500W
Standard Accessory	LED lamp, UV lamp x2, Base stand, Remote control, Foot switch, Drain valve, Waterproof sockets x2
Optional Accessory	Water and gas tap, Electric height adjustable base stand, Armrest, chair
External Size (WxDxH)	1100x750x2210 mm
Internal Size (WxDxH)	940x600x660 mm
Package Size (WxDxH)	1250x990x1770 mm
Gross Weight	265 kg
Consumption	600 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)