

MICROCENTRIFUGE CEN44-148



MICROCENTRIFUGE CEN44-148

This compact, powerful micro centrifuge is useful to separate or sediment small volume samples at high speed. The short-spin key, soft brake, FastTemp features optimizes the overall function of the centrifuges. Faults are diagnosed automatically and displays fault code. These hybrid micro-centrifuge can run PCR tubes, Capillary tubes along with standard tubes.

Used in Molecular Biology Separations, Clinical, Labs, Biochemistry, Tissue Culture, Genomics, Drug discover. Also known as Benchtop Centrifuge, Laboratory Centrifuge.

CEN44-148 MICROCENTRIFUGE

The maximum RCF can be 1700xg

Acceleration/Deceleration: <18 seconds

LCD display

Rotors are in autoclavable aluminium material

Short-spin key for quick centrifugation

Brushless DC motor

Low noise

Electronic lock

SPECIFICATIONS

Model	CEN44-148
Maximum Capacity (No of tubes x Vol.)	24x1.5/2ml
Speed Range	14800 rpm
Maximum RCF	17100xg
Time Range	15 S~99 min
Acceleration/ Deceleration	18s↑18s↓
Overall Dimension	230x210x150 mm
Weight (Net/Gross)	8 kg
Power	200 W
Power Supply	110V-240V 50-60 Hz

ACCESSORIES

Accessory Code	Name	Capacity
2202616005	Rotor	24x1.5/2.0 ml

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@m.labstac.com | Website: labstac.com