

# CLIMATIC CHAMBER CHA017-250A



# CLIMATIC CHAMBER CHA017-250A

## CHA017-250A CLIMATIC CHAMBER

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Microprocessor controller for temperature and humidity ensures of precise and reliable control

Imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement



## SPECIFICATIONS

Model	CHA017-250A
Capacity	250 L
Temperature Range	5-80°C
Display Resolution	0.1°C
Temperature Stability	High $\pm 0.5^{\circ}\text{C}$ Low $\pm 1^{\circ}\text{C}$
Temperature Uniformity	$\pm 2^{\circ}\text{C}$
Humidity Range	40-85%
Power Consumption	2300 W
Ambient Temperature	+5 - 35°C
Electrical Requirement	220 V 50 Hz
Interior Dimension	600Wx500Dx830H mm
Exterior Dimension	740Wx900Dx1580H mm
Shelves	3 pcs

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)