

CLIMATIC CHAMBER CHA018-0050A



CLIMATIC CHAMBER CHA018-0050A

CHA018-0050A CLIMATIC CHAMBER

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the height between the shelves in the chamber are adjustable

Homogeneity air circulating system

With temperature and humidity sensor

With programmable controller, large LCD screen

R134A refrigerant, With compressor and fan motor

A 25mm validation port on side of the chamber for easy testing operation and temperature validation

Over temperature and temperature deviation alarms

Compressor over-heat and over-load protections, fan motor over-heat and waterlock protections

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

SPECIFICATIONS

Model	CHA018-0050A
Capacity	50 L
Temperature Range	10-100°C
Temperature Accuracy	0.1°C
Temperature Stability	High temp: $\pm 0.5^{\circ}\text{C}$ Low temp: $\pm 1^{\circ}\text{C}$
Humidity control range	35-95%RH
Humidity Accuracy	$\pm 3\%RH$
Power Consumption	1700 W
Ambient Temperature	+5 - 35°C
Electrical Requirement	220 V 50 Hz
Interior Dimension	350Wx300Dx500H mm
Exterior Dimension	720Wx620Dx725H mm
Shelves	2 pcs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com