

STABILITY TEST CHAMBER CHA019-150B



STABILITY TEST CHAMBER CHA019-150B

CHA019-150B STABILITY TEST CHAMBER

Microprocessor control, stainless steel chamber, semicircular arcs at corners for easy cleaning

Even air circulating system

R134a refrigerant, 2 imported compressors and fan motor

Over temperature and temperature difference alarms

Imported humidity sensor which can be used in high humidity environment

Balance temperature and humidity adjusting system

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

UV light system for periodic sterilization of chamber.(Option)

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer record and inspect the parameters and the variations of temperature



SPECIFICATIONS

Model	CHA019-150B
Capacity	150 L
Temperature Range	0-65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C
Humidity control range	35-95%RH
Humidity Stability	±3%RH
Timing Range	1-99 hours each period
Humidity and temp adjusting	Balance temperature and humidity adjusting
Cooling system/cooling mode	Two sets of imported compressor work rotationally
Controller	Programmable(touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5-30°C
Electrical Requirement	AC 220 V 50 Hz
Power Consumption	2100 W
Interior Dimension	550Wx405Dx670H mm
External Dimension	690Wx805Dx1530H mm
Shelves	3 pcs
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com