

# STABILITY TEST CHAMBER CHA020-1000A



# STABILITY TEST CHAMBER CHA020-1000A

## CHA020-1000A STABILITY TEST CHAMBER

Microprocessor control, stainless steel chamber, semicircular arcs at corners for easy cleaning

Even air circulating system

R134a refrigerant, 2 imported compressors and fan motor

Over temperature and temperature difference alarms

Imported humidity sensor which can be used in high humidity environment

Balance temperature and humidity adjusting system

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

UV light system for periodic sterilization of chamber.(Option)

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer record and inspect the parameters and the variations of temperature



## SPECIFICATIONS

Model	CHA020-1000A
Capacity	1000 L
Temperature Range	0-65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C
Humidity control range	39-95%RH
Humidity Stability	±3%RH
Cooling system cooling mode	Two sets of imported compressor work rotationally
Controller	Programmable ( touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5-30°C
Electrical Requirement	AC 380 V 50 Hz
Power Consumption	7150 W
Interior Dimension	1050Wx590Dx1650H mm
External Dimension	1610Wx890Dx2000H mm
Shelves	4 pcs
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)