

# ILLUMINATING CLIMATE CHAMBER CHA11-150T1



# ILLUMINATING CLIMATE CHAMBER

## CHA11-150T1

Our chambers offer excellent temperature and lighting management for regulated growth of plants and different product. Its responsive humidification sensor and energy efficient style creates it a most popular selection for a large range of applications.

Used in Supports plant and insect growth, tissue cultivation, antibiotic cultivation and preservation and other controlled temperature experiments..

Also known as Humidity Chamber, Laboratory Climatic Chamber.

## CHA11-150T1 ILLUMINATING CLIMATE CHAMBER

Programmable microcomputer based PID controller with LCD display

Unique air circulation system ensures temperature uniformity

Mirror finished stainless steel inner chamber and cold-rolling steel with static spray plastics exterior

Double door design with built-in tempered glass viewing window

Built in high capacity intelligent humidification system

Automatic water replenishment by external tank

3-side illumination can be adjusted in five steps

Durable refrigeration system with small temperature fluctuation, auto defrosting and multiple layers security

Environment efficient, energy-saving Fluorine-free Refrigerant R134

Timer and over temperature alarm function



## SPECIFICATIONS

| Model                   | CHA11-150T1                            |
|-------------------------|--|
| Capacity                | 150 L                                  |
| Temperature Range       | 5-50°C (Light off), 10-50°C (Light on) |
| Temperature Accuracy    | ±0.5°C                                 |
| Temperature Uniformity  | ±2°C                                   |
| Temperature Fluctuation | ±2°C                                   |
| Temperature Resolution  | 0.1°C                                  |
| Temperature Sensor      | Pt 100Ω                                |
| Illumination Range      | 0-10000 lux                            |
| Timer Range             | 0-99h                                  |
| Control Steps           | 5 Steps                                |
| Shelves                 | 2                                      |
| Load per Shelf          | 10 kg                                  |
| Inner Dimension         | 800x500x380 mm                         |
| Overall Dimension       | 1350x640x660 mm                        |
| Weight (Net/Gross)      | 120/150 kg                             |
| Power                   | 900 W                                  |
| Power Supply            | 220V, 50Hz                             |



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@m.labstac.com](mailto:contact@m.labstac.com) | Website: [labstac.com](http://labstac.com)