

# ILLUMINATING CLIMATE CHAMBER CHA11-250T1



# ILLUMINATING CLIMATE CHAMBER

## CHA11-250T1

Our chambers offer excellent temperature and lighting management for regulated growth of plants and different product. Its responsive humidification sensor and energy efficient style creates it a most popular selection for a large range of applications.

Used in Supports plant and insect growth, tissue cultivation, antibiotic cultivation and preservation and other controlled temperature experiments..

Also known as Humidity Chamber, Laboratory Climatic Chamber.

## CHA11-250T1 ILLUMINATING CLIMATE CHAMBER

Programmable microcomputer based PID controller with LCD display

Unique air circulation system ensures temperature uniformity

Mirror finished stainless steel inner chamber and cold-rolling steel with static spray plastics exterior

Double door design with built-in tempered glass viewing window

Built in high capacity intelligent humidification system

Automatic water replenishment by external tank

3-side illumination can be adjusted in five steps

Durable refrigeration system with small temperature fluctuation, auto defrosting and multiple layers security

Environment efficient, energy-saving Fluorine-free Refrigerant R134

Timer and over temperature alarm function



## SPECIFICATIONS

Model	CHA11-250T1
Capacity	250 L
Temperature Range	5-50°C (Light off), 10-50°C (Light on)
Temperature Accuracy	±0.5°C
Temperature Uniformity	±2°C
Temperature Fluctuation	±2°C
Temperature Resolution	0.1°C
Temperature Sensor	Pt 100Ω
Illumination Range	0-15000 lux
Timer Range	0-99h
Control Steps	5 Steps
Shelves	2
Load per Shelf	10 kg
Inner Dimension	1000x550x450 mm
Overall Dimension	1550x690x660 mm
Weight (Net/Gross)	155/200 kg
Power	1000 W
Power Supply	220V, 50Hz



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)