

WATER CHILLER CHI07-05C



WATER CHILLER CHI07-05C

CHI07-05C WATER CHILLER

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean



SPECIFICATIONS

Model	CHI07-05C
Storage tank maximum capacity	5 L
Temperature range	-40-20°C
Ambient temperature range	+5-30°C
Temperature accuracy	±0.5°C
Cooling capacity at 20°C	1.95 Kw
Cooling capacity at 0°C	1.2 Kw
Cooling capacity at -20°C	0.65 Kw
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1500 W
Power requirements	AC220 V ± 10% / 50 HZ
Pump flow max.	8 L/min
Maximum head	1.5 m
Inlet/Outlet pipe diameter	Φ16
Noise level	≤45
Liquid tank opening / depth	Φ220x180 mm
Dimensions	315Wx540Dx625H mm

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@mail.labstac.com | Website: labstac.com