

TOP PRESS FREEZE DRYER FDR11-3MF

<u>aa</u>aa



TOP PRESS FREEZE DRYER FDR11-3MF

An ideal fit equipment for laboratory with a market proven design and the most advanced microprocessor control available on benchtop unit. It exceeds customer demand and is cost effective. It has Eco-friendly CFC free refrigeration system and provides higher performance.

Used in Laboratory, Research, Proteins, Organic Tissues, Waste Products, Plant Material, Polymers, Pharmaceuticals, Nutraceuticals, Plant material.

Also known as Benchtop Freeze Dryer, Tabletop Lyophilizer, Laboratory Benchtop Freeze Dryer, Laboratory Tabletop Lyophilizer, Benchtop Lyophilizer, Laboratory Benchtop Lyophilizer, Manifold Freeze Dryer.

FDR11-3MF TOP PRESS FREEZE DRYER

7 Inch color touch control LCD display Display run time & vacuum parameter The cold trap with freezing function eliminates the low temperature refrigerator Imported compressor, high capability of water-capture, low noise Mixed refrigerant, green environmental protection Built-in heat exchanger effectively reduces the temperature of cold trap Anti-return oil vacuum pump to prevent the pollution of the material Transparent bell-cap drying room is safe and visual Optional distribution defrosting function Optional nitrogen inflating valve



SPECIFICATIONS

Model	FDR11-3MF
Туре	Manifold
Drying area	0.092 m ²
Тгау	200 x 3 mm
Tray capacity Condensor	1L
No-load temperature	<-55°C (-80 optional)
Vacuum	< 10 Pa
Interlayer spacing	70 mm
Vials number for reference	165 (22) 285 (16) 560 (12)
Ability to capture Water	3 kg
Machine Size	500x400x370 mm
Power	850 W
Voltage	220V/50Hz or 110V/60HZ



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com