

AUTOMATIC AIR GENERATOR GEN13-1000



AUTOMATIC AIR GENERATOR GEN13-1000

Air Generator is designed for removing hydrocarbons from the air stream and produces pure, hydrocarbon free and dry air, with a very low dew point. Long service life, easy maintenance, abrasion resistant, cost effective, performance, quick and easy servicing are some of the features which makes it convenient for the laboratory.

Used in Pharmaceutical, Gas Chromatography Detectors, Petrochemical, Laboratory, Medical, Research, Industries, Environmental, Clinical, Forensics..

Also known as Laboratory Air Generator.

GEN13-1000 AUTOMATIC AIR GENERATOR

The hydrocarbon is changed into carbon dioxide and vapor in the catalyzer with Pt-Pd carrier

Increased gas output quality

Compact design, easy using, automatically operation, safety



SPECIFICATIONS

Model	GEN13-1000
Output air concentration	<0.1PPM
Input air concentration	<100PPM
Maximum Output Pressure	0-0.6 Mpa
Maximum Flow Rate	1000 ml/min
Power Supply	220V±10% 50~60Hz
Consumption Power	150 W
Working Temperature	400-450°C
Environmental Temperature	0-40°C
Humidity	<85%
Dimension	400x360x220 mm
Net Weight	12 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com