

GENERAL PURPOSE INCUBATOR INC081-243



GENERAL PURPOSE INCUBATOR INC081-243

INC081-243 GENERAL PURPOSE INCUBATOR

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature



SPECIFICATIONS

Model	INC081-243
Capacity	243 L
Electrical requirement	220 V 50 Hz
Controller	LCD Programmable controller
Temperature Range	RT+5°C - 80°C
Display Resolution	0.1°C
Temperature Stability	±0.2°C
Ambient Temperature	+5 - 35°C
Power Consumption	600 W
Interior Dimension	600Wx450Dx900H mm
Exterior Dimension	755Wx785Dx1130H mm
Shelves	2 pcs
Timing Range	0~5999 min

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com