

NATURAL CONVECTION INCUBATOR INC082-010



NATURAL CONVECTION INCUBATOR

INC082-010

INC082-010 NATURAL CONVECTION INCUBATOR

P.I.D temperature controller provides accurate and reliable temperature control

Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage

Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed

Volume(10L~210L)

Inner chamber is made from corrosion-resistant mirror stainless steel

Round curved inner angle is easy to clean

Anti-skid shelf design, easy to operate by single hand

Auto Start Feature after power loss/return

Temperature deviation alarm

Over current protection alarm

Independent Over-temperature protection meets DIN 12880 International standard requirements provides you double protection



SPECIFICATIONS

Model	INC082-010
Capacity	10 L
Electrical requirement	220 V 50 Hz
Temperature Range	Amb +5 - 65°C
Display Resolution	0.1°C
Ambient Temperature	+5 - 35°C
Power Consumption	85 W
Inner glass door	None
Viewing window	Has
Interior Dimension	250Wx200Dx200H mm
Exterior Dimension	460Wx300Dx330H mm
Shelves	2 pcs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com