

# COOLED INCUBATOR INC083-0778



# COOLED INCUBATOR INC083-0778

## INC083-0778 COOLED INCUBATOR

304 stainless steel, mirror polishing processing, easy to clean and maintain

PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability

The inner lamp for observation of the samples is standard supplied

3 fan speed meets all requirements of different experiments

Famous brand compressor with refrigerant R134a



## SPECIFICATIONS

Model	INC083-0778
Capacity	778 L
Temperature Range	0 - 60°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Temperature Uniformity	$\pm 2.5^{\circ}\text{C}$
Electrical Requirement	220 V 50 Hz
Ambient Temperature	+5°C - 30°C
Power Consumption	4100 W
Interior Dimension	800Wx590Dx1650H mm
Exterior Dimension	1475Wx890Dx1780H mm
Shelves	3 pcs
Timing Range	0~5999 min
Display	LCD

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)