

LABSTAC

COOLED INCUBATOR INC083-1500



labstac.com

COOLED INCUBATOR INC083-1500

INC083-1500 COOLED INCUBATOR

304 stainless steel, mirror polishing processing, easy to clean and maintain

PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability

The inner lamp for observation of the samples is standard supplied

3 fan speed meets all requirements of different experiments

Famous brand compressor with refrigerant R134a



SPECIFICATIONS

Model	INC083-1500
Capacity	1500 L
Temperature Range	0 - 60°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Temperature Uniformity	$\pm 2.5^{\circ}\text{C}$
Electrical Requirement	380 V 50 Hz
Ambient Temperature	+5°C - 30°C
Power Consumption	5000 W
Interior Dimension	105Wx590Dx1650H mm
Exterior Dimension	2110Wx890Dx2050H mm
Shelves	3 pcs
Timing Range	0~5999 min
Display	LCD

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com