

COOLED INCUBATOR INC085-250



COOLED INCUBATOR INC085-250

INC085-250 COOLED INCUBATOR

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Latest PID controller

R134a refrigerant, imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement



SPECIFICATIONS

Model	INC085-250
Capacity	250 L
Temperature Range	-10°C - 65°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Electrical Requirement	220 V 50 Hz
Ambient Temperature	+5°C - 35°C
Power Consumption	1500 W
Interior Dimension	600Wx500Dx830H mm
Exterior Dimension	740Wx900Dx1580H mm
Shelves	3 pcs
Timing Range	0~9999 min

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com