

BIOLOGICAL INDICATOR INCUBATOR INC51-100



BIOLOGICAL INDICATOR INCUBATOR INC51-100

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small in size, less weight and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator and other biological indicator sterilization, effect detection and cultivation.

Used in Environmental protection, Research institutes, University laboratories.

Also known as Laboratory Incubator.

INC51-100 BIOLOGICAL INDICATOR INCUBATOR

Unique designed. Small size, light weight, portable, and suits on various occasions.

LCD display. Temperature and time display simultaneously.

Auto fault detect and buzzer alarm. Temperature calibration function.

24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.

Timer function. Time range from 0 to 999 min.

Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.



SPECIFICATIONS

Model	INC51-100
Temperature Control Range	RT+5°C~100°C
Temperature Setting Range	5°C~100°C
Temperature Stability@56°C	±0.5°C
Temp. Display Accuracy	0.1°C
Heating Speed	<6min (20°C to 56°C)
Time Range	1sec~999sec or 1min~999min
Voltage	DC 24V adapter
Power	60W
Dimension (WxDxH)	110x156x92 mm
Net Weight	1kgs

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
2805514005	Block C	6 x Φ15 mm
2805514006	Block D	6 x Φ16mm
2805514007	Customized	Customized



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com