

# MICROBIOLOGICAL INCUBATOR INC64-400



# MICROBIOLOGICAL INCUBATOR INC64-400

Microbiological Incubator can be used for many applications beyond traditional bacterial culture, such as temperature dependent incubations, enzymatic reactions or for reagent storage. Programmable controls and refrigeration are some of the additional features available in incubators on the market today.

Used in Temperature dependent incubations, Enzymatic reactions, Reagent Storage. Programmable controls, Refrigeration.

Also known as Laboratory Microbiological Incubator.

## **INC64-400** MICROBIOLOGICAL INCUBATOR

ALLCOLD Refrigeration Technology: Auto defrost, multiple security system, long time running, environmental protection, high efficiency and energy saving, Auto-defrost function, Imported DuPont SUVA R134 a environmental refrigerant.

ALLIGENT Humidification System: Automatic water intake, automatic water level control, persistent

ALLFLOW Perfect Air Current Cycling: Perfect forced convection, maximum number of working room, minimum temperature recovery time after the opening, world famous axial fan, perfect air current design.

ALLSENS Programmable PID Control: Adaptive PID controller precisely controls the temperature and humidity, prevent temperature soaring, keep working room temperature stable and uniformity.

Excellent Imported temperature and humidity Sensor.

Efficient isolation Design



### **SPECIFICATIONS**

Model	INC64-400
Capacity	400 L
Temperature Range	0-65°C
Ambient Temperature	10~30°C
Temperature Fluctuation	±0.5 at 10-40°C
Temperature Uniformity	±1.5
Temperature Resolution	0.1℃
Relative Humidity	Below 70%
Sterilization Function	Yes
Humidity Range	40-95 %RH
Humidity Fluctuation	±2 RH
Interior	SUS304 Stainless Steel Materials
Heat insulator material	Imported environmental protection material
Timer Range	0-99 hrs, 0-9999 min
Convection Mode	Forced Convection
Internal Dimension	601Wx639Dx105H2 mm
Exterior Dimension	745Wx930Dx1700H mm
Package Size	815x1090x1907 mm
Shelves/Trays	4
Weight	158.5/188 kg
Power	1350 W

labstac.com

2

Power Supply Single phase AC220 V/50 Hz



### **Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@mail.labstac.com | Website: labstac.com