

THERMOSTATIC HEATING INCUBATOR INC83-130

<u>aaaa</u>

labstac.com

THERMOSTATIC HEATING INCUBATOR

INC83-130

General Purpose Incubator are designed to accommodate an ample range of laboratory applications and lends a contamination-free environment for cell and tissue cultures. These incubators serve the purpose for most biological analysis, research, general laboratory applications, biochemical studies, bacteriology, and hematological studies. Used in Quality Control, Medicine Processing Industries, Research, Pharmaceuticals, Microbial Culturing. Also known as Lab Incubator, Laboratory General Purpose Incubator.

INC83-130 THERMOSTATIC HEATING INCUBATOR

ALLHEAT Cavity Warm-up Technology: Uniform distribution of heat, low energy consumption, heat not easily lost, low cost

ALLFLOW Perfect Air Current Cycling: Perfect forced convection, maximum number of working room, minimum temperature recovery time after the opening, world famous axial fan, perfect air current design.

ALLSENS Programmable PID Control: Adaptive PID controller precisely controls the temperature and humidity, prevent temperature soaring, keep working room temperature stable and uniformity.

Pro-Insulation Insulation Technology: Good silicon door seal, isolation type hinge design, buckle door handles, sealability

Excellent Imported temperature and humidity Sensor.

Efficient isolation Design



SPECIFICATIONS

| Model | INC83-130 |
|-------------------------|------------------------------------|
| Capacity | 130 L |
| Temperature Range | RT +3°C ~ 65°C |
| Ambient Temperature | 10~30°C |
| Temperature Accuracy | 0.1°C |
| Temperature Fluctuation | ≤±0.5°C (3~50°C) |
| Temperature Uniformity | ±1°C (3~50°C) |
| Ambient Humidity | <70% |
| Interior | SUS304 Stainless Steel Materials |
| Timer Range | 0-99 hrs, 0-9999 min, can be chose |
| Convection Mode | Forced Convection |
| Internal Dimension | 550Wx450Dx550H mm |
| Exterior Dimension | 780Wx693Dx770H mm |
| Package Size | 860x780x890 mm |
| Shelves/Trays | 2 standard |
| Weight | 65/69 kg |
| Power | 670 W |
| Power Supply | Single phase AC220 V/50 Hz |



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com