

HORIZONTAL LAMINAR AIR FLOW LAF22-1389



HORIZONTAL LAMINAR AIR FLOW LAF22-1389

They are designed to provide a clean air environment for research operation which required complete anti-bacterial working area. Small size saves precious laboratory space and maintains constant positive pressure inside the cabinet which prevents intake of contaminated air.

Used in Bioscience, Food processing, Pharmaceuticals, Aerospace, Medical research Laboratories, Hospitals, Research. Also known as Minimal-Turbulence Air Flow, Laboratory Laminar Flow, Clean Bench, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Tissue Culture Hood, Laminar Air Flow Cabinet, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF22-1389 HORIZONTAL LAMINAR AIR FLOW

ETL certification, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm (Abnormal airflow velocity).



SPECIFICATIONS

Model	LAF22-1389
AirFlow Velocity	80~99fpm
HEPA Filter	One,99.995% efficiency at 0.3um
Pre filter	Polyster fibre, Washable
Work Surface Height	750 mm
Main Body Material	1.0 mm Cold-rolled steel with anti-bacteria powder coating.
Work Table Material	304 Stainless steel
Front Window	5 mm toughened glass, anti-UV.
Display	LCD display
Waterproof Socket	One socket (Double type), America standard, Max.Power: 500W
LED Lamp	18Wx1
Standard Accessory	Manually height adjustable base stand,LED lamp, wind speed sensor, waterproof socket , Stainless Steel LV.Bar with 10 hooks
Optional Accessory	UV lamp
Noise	268dB(A)
External Size	1500x810x (1720~1980)mm
Internal Size	1400Wx500Dx600H mm
Package Size	1640Wx1090Dx1250H mm
Gross Weight	265kg
Consumption	950W
Power Supply	103.5-126.5V, 60Hz, 10A

ACCESSORIES

Accessory Code	Name
5900509005	Fluorescent lamp
5900509006	UV lamp
5900509007	Base stand
5900509008	Waterproof socket

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com